

Product Description	A Modern Water based low Sheen which has been especially formulated to give the best long term performance for the coating of Interior/Exterior Masonry Surfaces.	
Application Areas	<ul style="list-style-type: none"> • Hardboard and fibre cement boards. • Cement Plastered Surfaces • Primed metal and wooden substrates. 	
Product Features	<ul style="list-style-type: none"> • High hiding power, Very Durable Low Sheen Finish for Interior/ Exterior use. • Excellent adhesion and hiding power. • Excellent, no mess application properties. • Quick Drying 2 Coats in one day. • Low odour • Stain resistant and washable. 	
Product Data	Resin Base	Pure Acrylic
	Drying Time	Touch dry: 2-3 hour Hard dry:/re coating time 4-5 hours
	Dry Film Thickness	30-40 microns per coat
	Spreading Rate	8-10SQM per 1 litre Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 6-8 square metres per litre for the first coat and 9-11 square metres per litre for subsequent coats and for when applied to sealed, previously painted substrates.
Application Details		
• Mixing	Always stir well before use with a flat paddle.	
• Application Method	Brush, Roller	
• Thinning	This Product is ready for use un-thinned; Thinning with Water will reduce obliterating power and is not recommended	
• Cleaning	Application equipment clean-up is with clean water	
• Application	<ul style="list-style-type: none"> • Stir well before use. • With brush, Roller apply a generous coat of the Geo Paint Low Sheen to the area that needs protecting. • Allow to dry at least 4 hours before recoating • Clean tools immediately after use with Water • Do not apply before 09:00 and after 16:00 in the winter. • Do not apply exterior if it looks like rain will occur with in 4-6 hours of application. 	
Surface Preparation		
• Rusted Metal	<ul style="list-style-type: none"> • Remove any rust and mill scale from steel surface. • Affected areas need to be cleaned back to bright metal • Apply one coat of Geo Paint Water Based Etch Primer, leave to dry overnight and apply a coat of Geo Paint Universal Undercoat and allow to dry overnight. Lightly sand and remove all traces of dust by washing and allowing to dry. • Apply two coats of Geo Paint Low Sheen allowing at least 4 hours to dry between Coats. 	
• New Metal (Galvanized Steel)	<ul style="list-style-type: none"> • Degrease surfaces with an abrasive Degreaser to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break free. • After drying Apply one coat of Geo Paint Water Based Etch Primer, leave to dry overnight. • Apply two coats of Geo Paint Low Sheen allowing at least 4 hours to dry between Coats 	
• Previously Painted Surfaces	<ul style="list-style-type: none"> • Make sure old paint coatings are firm and solid. • Remove all loose, flaking and bubbling paint. • Remove all dust, grease, foreign material, fungal and algae growth. • Prime with Geo Paint Plaster Primer SR or Geo Paint Water Based Plaster Primer SR. • Apply 2 Coats of Geo Paint Low Sheen allowing at least 4 hours to dry between Coats 	
• Cement Plastered Walls	<ul style="list-style-type: none"> • Moisture Content should be 9% Max • Prime with Geo Paint Plaster Primer SR or Geo Paint Water Based Plaster Primer SR. • Apply 2 Coats of Geo Paint Low Sheen allowing at Least 4 Hours between Coats 	
Colour Range and Quantities	<ul style="list-style-type: none"> • White and Colours Tinted on the Geo paint Tinting system • Available in 5 and 20 litres. 	

Precautions	<ul style="list-style-type: none"> • This Product is Not Flammable and contains no Toxic Substances/VOC (EU VOC Regulations) • Do not eat/drink or smoke whilst applying the paint • Use in well ventilated areas
Disclaimer	<p>The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our experiences and tests and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and condition of the substrate prior to painting are beyond our control. Geo-Paint (Pty) Limited accept no responsibility or accountability for either the workmanship in surface preparation or the application of our products. Should the reader wish to use the general specification for a PARTICULAR project, then he should first confirm with our Technical Service Department that the specification can be used. NB: IT IS THE RESPONSIBILITY OF THE USER TO ENSURE THAT THE LATEST TDS IS BEING USED, AND THAT IT HAS NOT BEEN SUPERSEDED. We cannot take any responsibility where this precaution has not been taken.</p>
Geo Paint	
+27-18-2932274	wayne.geotechsa@telkomsa.net