

<b>Product Description</b>	Geo Paint Matt	
<b>Application Areas</b>	<ul style="list-style-type: none"> <li>• Primed Wood/Metal</li> <li>• Primed Cement Plaster or Fibre Cement</li> <li>• Previously painted substrates.</li> <li>• Exterior</li> </ul>	
<b>Product Features</b>	<ul style="list-style-type: none"> <li>• This Product is a Traditional Matt Wall Paint</li> <li>• Good durability and UV resistant for the harsh RSA climate.</li> <li>• Highly water resistant</li> <li>• Excellent adhesion/Flexibility</li> <li>• Excellent, no mess application properties.</li> <li>• Quick drying 2 coats can be applied in one day.</li> <li>• If correctly applied to a properly prepared substrate, the product has a life expectancy of 5 Years, possibly longer. The use of a special polymer not only improves Durability but also properties like water resistance and dirt shedding</li> </ul>	
<b>Product Data</b>	<b>Resin Base</b>	Styrene Acrylic
	<b>Drying Time</b>	Touch dry: ± 1 hour Hard dry: ± 4-6 hours
	<b>Film Thickness</b>	30-40 microns per coat
	<b>Spreading Rate</b>	8-10 SQM per 1 litre Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 6-8 square meters per litre for the first coat and 9-11 square meters per litre for subsequent coats and for when applied to sealed, previously painted substrates.
<b>Application Details</b>		
• <b>Mixing</b>	Always stir well before use with a flat paddle.	
• <b>Application Method</b>	<ul style="list-style-type: none"> <li>• Brush, Roller and Airless Spray</li> </ul>	
• <b>Thinning</b>	This Product is ready for use un-thinned; thinning with water will reduce its hiding power.	
• <b>Cleaning</b>	Application equipment clean up is with clean tap water.	
• <b>Application</b>	<ul style="list-style-type: none"> <li>• Stir well before use.</li> <li>• With brush or roller apply a generous coat of Geo Paint Matt to the area that needs protecting.</li> <li>• Allow to dry 3-4 hours before recoating.</li> <li>• With a Brush or roller apply a second generous coat.</li> <li>• 2 Coats of Geo Paint Matt are used for best results.</li> <li>• This Product is ready for use un-thinned; thinning with water will reduce its hiding power.</li> <li>• Clean tools immediately after use with clean tap water.</li> <li>• Do not apply before 09:00 and after 16:00 in the winter.</li> <li>• Do not apply exterior if it looks like rain will occur within 4-6 hours of application.</li> </ul>	
<b>Surface Preparation</b>		
• <b>Rusted Metal</b>	<ul style="list-style-type: none"> <li>• Affected areas need to be cleaned back to bright metal and spot primed with Geo Paint Water based Metal Primer.</li> <li>• Remove collected sand and dust from the area.</li> <li>• Apply two coats of Geo Paint Matt</li> </ul>	

<ul style="list-style-type: none"> <li>• <b>New Metal</b></li> </ul>	<ul style="list-style-type: none"> <li>• Degrease surfaces with a Galvanized Iron Cleaner to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break free.</li> <li>• Rinse well with potable water.</li> <li>• Prime the Clean Degreased Metal with Geo Paint Water Based Metal Primer</li> <li>• Apply two coats of Geo Paint Matt.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Wood</b></li> </ul>	<ul style="list-style-type: none"> <li>• Prime with Geo Paint Universal under Coat.</li> <li>• Lightly Sand, wipe off dust.</li> <li>• Apply two coats of Geo Paint Matt.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Uncoated cement Plaster surfaces</b></li> </ul>	<ul style="list-style-type: none"> <li>• Remove dust, foreign material, fungal and algae growth.</li> <li>• Fill all visible cracks and seal with Geo Paint Water Based Plaster Primer SR.</li> <li>• Apply two coats of Geo Paint Matt.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Fibre Cement Surfaces (Uncoated, Weathered or New)</b></li> </ul>	<ul style="list-style-type: none"> <li>• Remove dust, foreign material, fungal and algae growth.</li> <li>• If friable or powdery, seal with Geo Paint Bond It or Water Based Plaster Primer SR.</li> <li>• Apply two coats of Geo Paint Matt</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Previously Painted Surfaces</b></li> </ul>	<ul style="list-style-type: none"> <li>• Make sure old paint coatings are firm and solid.</li> <li>• Remove all loose, flaking and bubbling paint.</li> <li>• Remove all dust, grease, foreign material, fungal and algae growth.</li> <li>• Allow to dry.</li> <li>• If then powdery or friable, seal with Geo Paint Bond It or Water Based Plaster Primer</li> <li>• Apply two coats of Geo Paint Matt</li> </ul>
<b>Colour Range and Quantities</b>	<ul style="list-style-type: none"> <li>• This Product is can be tinted in a range of Colours</li> <li>• Available in 1, 5 and 20litres.</li> </ul>
<b>Precautions</b>	<ul style="list-style-type: none"> <li>• This Product is not flammable, contains no toxic substances and only low levels of VOC (EU regulations).</li> </ul>
<b>Disclaimer</b>	<p><i>The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our experiences and tests and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and condition of the substrate prior to painting are beyond our control. Geo-Paint (Pty) Limited accept no responsibility or accountability for either the workmanship in surface preparation or the application of our products. Should the reader wish to use the general specification for a PARTICULAR project, then he should first confirm with our Technical Service Department that the specification can be used. NB: IT IS THE RESPONSIBILITY OF THE USER TO ENSURE THAT THE LATEST TDS IS BEING USED, AND THAT IT HAS NOT BEEN SUPERSEDED. We cannot take any responsibility where this precaution has not been taken.</i></p>
<b>Geo Paint</b>	
+27-18-2932274	wayne.geotechsa@telkomsa.net